

CITIZEN

High speed POS printing with front exit

Hospitality highest standard



LCD display

The industry's first POS printer with LCD display for easy configuration and operation. Many set up options and coloured status or error messages.

In a hurry?

With 300mm/sec. print speed the CT-S851II is the fastest POS printer in the market.

Tool-free maintenance

Paper jam? No problem for the CT-S851II. One hand grip and the cutter is released automatically. No tool is needed. Even if the long-life cutter ever needs to be exchanged. Thanks to it's Snap-In design this only takes 30 seconds.

CT-S851II

POS, Receipt printer (thermal 3 inch / 80mm)

Applications

- Hospitality
- Kiosk
- Kitchen
- Retail



High speed printing with unique ease of use

CITIZEN

Specifications

Model	CT-S851II
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	300 mm/sec.
Print Width (maximum)	45 / 48 / 52 / 54 / 64 / 68 / 72 / 80 mm
Media Width (min to max)	58 / 60 / 80 / 83 mm (+/- 1mm)
Roll Size (max), Core Size	83 mm outside diameter
Media Thickness (min to max)	65 to 75 ?m or 75 to 150 ?m or 85 to 150 ?m
Main Interface	None: interface card slot for optional card
Interface	Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN, Premium Wireless LAN, Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), USB, USB with hub, Powered USB, External device port, RJ-45, 8-pin connector
Power supply	100 - 240V, 50/60hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Cutter	Guillotine type, full and partial

CT-S851II

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification - built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packaging
- Tool-free maintenance



CITIZEN

CT-S851II

POS, Receipt printer (thermal 3 inch / 80mm)

Model	CT-S851II
--------------	------------------

EMC and safety standards

CE, TUV, UL, C-UL, FCC class A

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0