
CITIZEN

Citizen PD24

Stylish, Compact And **Portable Printing**



0000 Bluetooth®, IrDA, USB and RS232C interfaces as standard Light weight and ultra compact, from 440 grams

4-inch wide thermal receipt printing

Range of power sources, options and accessories

0

CITIZEN

Citizen PD24

Citizen's PD24 is the first in the next generation of stylish ruggedised portable printers. Whether your application is printing receipts for

customers, packing lists for products or messages sent to your PDA, the PD24 is an ideal partner.

Fast And Quiet

The high-speed thermal head of the PD24 allows printing at up to 2 inches per second. So, as an example, a receipt about 6 inches or 150mm long can be printed in just 3 seconds.

Bluetooth® Connectivity

The PD24 features a full range of interfaces including the industry standard Bluetooth® wireless interface. All printers also include IrDA (infra-red), USB and RS232C serial interfaces as standard.

Ease-Of-Use As Standard

Like all Citizen printers, we "design in" ease-of-use from the initial concept of our printers. Whether it is the easy-to-load clamshell mechanism or the integral VuePrintTM

menu system for quick configuration, the PD24 is simplicity itself to setup and use.

More Power To You

The PD24 can be operated from a number of different power supplies. As standard, there is the easy-to-change internal Lithium Ion battery and, included in the standard pack, is an AC adapter which will both power the printer and charge the batteries.

Alternatively, you can choose the optional two-station

external battery charger to refill batteries between shifts.

In Vehicle Specialists

If you are a truly mobile user, a car power adapter is also available to operate and/or charge your printer. Should you want to mount the printer in to a truck or van, we've also made sure that there are two secure mounting points of the bottom of the printer to allow you to mount it in your vehicle.



Accessories And Options

Other options and accessories include a range of carry cases and belt clips as well as Citizen's specific serial and USB cables. Full details of all of these on request.

- * Bluetooth can be 'omitted' as a factory option on request. Bluetooth $^{\scriptscriptstyle (\!0\!)}$ is a registered trademark of the Bluetooth SIG, Inc.
- † The exact specification and availability of this item is subject to change and/or improvement at any time
- All trademarks are acknowledged. Errors & omissions excluded. Note: These specifications are subject to change without notice.
 Copyright © Citizen Systems Europe 2005

Technical Specification: PD24

recinical Specificati		
Technology	Direct thermal	
Resolution (dot pitch)	8 dots/mm, 203 dpi	
Printhead dot count	832 dots	
Maximum Print Speed	400 dot lines / second	
Equivalent to	2 inches / second (approx)	
Conditions	5% coverage, density setting 0	
Head life	30 million pulses (12.5% coverage, density 0)	
Print Width	104 mm, 4.09 inches	
Media Width	112 mm, 4.41 inches	
Media Types	Roll, cut sheet, multi-copy paper	
Integral Paper Roll	50 mm, 1.97 inches maximum OD	
Core Size	8.5 mm / 0.33 inches minimum ID	
Case type	Elastomer overmoulded plastic	
Mechanism type	Easy-to-load clam shell	
Interfaces	Bluetooth®* IrDA Infrared RS232C USB	
Input Buffer	64 Kb	
Emulations	ESC/P, Citizen original commands, ESC/POS (barcode commands only)	
User Interface Configuration method	3 keys (Menu, Feed, Power) 3 LEDs (Power, Status, Error) VuePrint™ menu system	
Battery Type	Li-lon cell	
Voltage & capacity	Typically 7.2v, 1800 mAh [†]	
Print capacity	25,000 lines (minimum)	
Conditions	ASCII pattern, full battery, density 0	
Dimensions (W x D x H)	147 x 140 x 63 mm 5.79 x 5.51 x 2.48 inches Values include media roll, mounts and projections	
Typical weight	740 g (printer, battery, full paper roll)	
Printer weight	440 g	
Battery pack weight	100 g	
Full paper roll weight	200 g	
AC charger weight	222 g (excluding power cord)	
Operating Temperature	+5°C to +40°C (guaranteed print quality)	
Operating Humidity	30% to 90% RH, non-condensing	
Storage Temperature	-25°C to +60°C	
Options & Accessories	RS232 cable USB cable Additional battery Soft carry case, belt clips and straps† External 2-station battery charger† Car adapter / charger†	

Citizen Systems Europe UK
Park House, 643 - 651 Staines Road
Feltham. Middlesex. TW14 8PA. United Kingdom
Tel: +44(0)20 8893 1900 Fax: +44 (0)20 8893 0080

Citizen Systems Europe GmbH

Mettinger Straße 11, D-73728 Esslingen, Deutschland
Fon: +49(0) 711 3906 420 Fax: +49 (0)711 3906 405

sales@citizen-europe.com www.citizen-europe.com

\ - L - :	•	agui	
регат	ıer	unn	П.
ומוא	101	כונונוכ	н.

1200350 PD24-e1-0405